



TACK



IN

Precision Machining Industrial

KATALOG

TRAČNE ŽAGE

TRAČNE PILE

+ / TESTERE





BS-712N



BS-1018B



BS-712R



BS-115



BS-912B

Features:

- ✳ Vertical force controlled through hydraulic cylinder
- ✳ Strong structure for big capacity cutting

Lasnosti:

- ✳ Navpično silo rezanja, kontrolira hidravlični valj
- ✳ Močna, čokata struktura za rezanja velike zmogljivosti in dolga časa uporabe

Karakteristike:

- ✳ Vertikalnu silu rada kontrolišemo pomoću hidravličnog cilindra
- ✳ Jaka konstrukcija kućišta za veliku sposobnost rezanja i dugi vijek trajanja

The bow can be swiveled between 45° and 90°
 Delovni lok žage se lahko zasuka med 45° in 90°
 Radni luk pile/testere se može postavljati između 45° i 90°

| SPECIFIKACIJE | Specification | BS - 115 | BS - 712N | BS - 712R | |
|---|---------------|-------------------|---------------------------------|------------------------|----------------------|
| Kapaciteta OKROGLI PRAVOKOTNI PRAVOKOTNI PRAVOKOTNI | Capacity | Circular@90° | 115mm | 178mm(7") | 178mm(7") |
| | | Rectangular@90° | 100x150mm | 178x305mm(7"12") | 178x210mm(7"x8.25") |
| | | Circular@45° | 75mm | 127mm(5") | 127mm(5") |
| | | Rectangular@45° | 70x60mm | 120x125mm(4.75"x4.88") | 85x140mm(3.33"x5.5") |
| Hitrost rezila Brzina rezanja | Blade speed | @60HZ | 24,36,61MPM | 27, 41, 59, 78 MPM | 27, 41, 59, 78 MPM |
| | | @50HZ | 20,29,50MPM | 22, 34, 49, 64 MPM | 22, 34, 49, 64 MPM |
| Velikost rezila Velikina reznog traka | Blade size | 12.5 x 0.6x1638mm | 19 x 0.9x2362mm | 19x0.9x2362mm | |
| Moč motorja Snaga motora | Motor power | 370w(1PH) | 750w 1HP(3PH), 1.1kw 1.5HP(1PH) | | |
| Pogon | Drive | V-Belt | V-Belt | V-Belt | |
| Dimenzije paketa Dimenzije paketa | Packing size | 1020x320x390mm | 1250x510x1150mm | 1290x730x1150mm | |
| Neto/bruto teža Neto/bruto težina | N.W/G.W | 61/84kgs | 145/178kgs | 170/192kgs | |

| SPECIFIKACIJE | Specification | BS - 912B | BS - 1018B | |
|---|---------------|-----------------------|--------------------|--------------------|
| Kapaciteta OKROGLI PRAVOKOTNI PRAVOKOTNI PRAVOKOTNI | Capacity | Circular@90° | 229mm(9") | 254mm(10") |
| | | Rectangular@90° | 178x305mm(7"x12") | 127x457mm(5"x18") |
| | | Circular@45° | 150mm(6") | 150mm(6") |
| | | Rectangular@45° | 127x150mm(5"x6") | 150x190mm(6"x7.5") |
| Hitrost rezila Brzina rezanja | Blade speed | @60HZ | 32, 60, 88, 115MPM | 35,60,88,115MPM |
| | | @50HZ | 26, 50, 73, 95MPM | 29,50,73,95MPM |
| Dimenzije rezila Dimenzije reznog traka | Blade size | 27x0.9x2655mm | 27x0.9x3280mm | |
| Moč motorja Snaga motora | Motor power | 1.1kw 1.5HP (3PH,1PH) | 1.5kw 2HP(3PH) | |
| Pogon | Drive type | V-Belt | V-Belt | |
| Dimenzije paketa Dimenzije paketa | Packing size | 1540x590x1150mm | 1830x830x1150mm | |
| Neto/bruto teža Neto/bruto težina | N.W/G.W | 230/260kgs | 310/385kgs | |

Vse pravice pridržane ! v SLO ali JSJ jezicah !!

Sva prava zadržana u SLO i JSJ jezicima !!



GH4235

Features:

- ✳ Double column structure vertical lifting with high stability
- ✳ The cutting speed is variable and hydraulic
- ✳ Workpiece is clamped by hydraulic control and easy to operate
- ✳ Hydraulic clamping on three axis is optional

Lasnosti :

- ✳ Vertikalno hidravlično dviganje na dveh stolpcih z visoko stabilnostjo
- ✳ Hitrost rezanja variabilna / spremenljiva in hidravlična
- ✳ Obdelovanec je vpet s hidravličnim nadzorom in enostaven za upravljanje
- ✳ Hidravlično vpenjanje v tri osi - OPCIJA

Karakteristike :

- ✳ Vertikalno hidravlično podizanje na dva stupa sa visokom stabilnostjo
- ✳ Brzina rezanja je hidravlično variabilna / promjenljiva
- ✳ Obradak se hidravlično steže a upravljanje je jednostavno
- ✳ Hidravlično stezjanje obradka je moguće i sa tri osi - OPCIJA



GH4220A



GH4250



GH4280



Karbo. konstruk. jeklo
Ugljič. konstr. čelik

Nizleži. jeklo
Niskolegira.čel

Visokoleg. jeklo
Visokolegi. čelik



Posebnolegir. jekla
Posebno legir. čelici

Nerjaveče jeklo
Nehrđa. čelik

Odporni jekl. za OSi
Odporni čelici na habanje za OSOVINE

| SPECIFIKACIJE | Specification | GH4220A | GH4228A | GH4235 | GH4240 | GH4250 | GH4270 | GH4280 | GH42100 |
|---|-----------------------------|-----------------|-------------------------|-----------------------------------|-------------------|--------------------------|----------------------|--------------------|---------------------|
| PREMIER MAKSIM. REZANJA OKROGLO | Cutting range (round) | Φ200mm | Φ280mm | Φ350mm | Φ400mm | Φ500mm | Φ700mm | Φ800mm | Φ1000mm |
| PROMIJER MAKSIMALNOG REZANJA OKROGLO | Cutting range (rectangular) | 200x200mm | 280x280mm | 350x350mm | 400x400mm | 500x500mm | 700x700mm | 800x800mm | 1000x1000mm |
| MAKSIMALNO REZANJE STIRJUGLATO | Blade size (LxWxT) | 2800x27x0.9mm | 3505x27x0.9mm | 4115x34x1.1mm | 5000x41x1.3mm | 5800x41x1.3mm | 7205x54x1.6mm | 8820x54x1.6mm | 9820x67x1.6mm |
| MAKSIMALNO REZANJE KVADRATNO | Blade feed type | | hydraulic stepless | HIDRAVLIČNO STALNO (NEPREKINJENO) | | HIDRAVLIČNO KONTINUIRANO | | hydraulic stepless | |
| DIMENZIJE REZILA (dOL. x SIR. x DEBL. mm) | Blade tension type | | manual | | | manual | | hydraulic | |
| DIMEN. REZNOG TRAKA (Duž. x Visin. x Deblj. mm) | Blade linear speed | | 27/45/69m/min | | | 27/45/69m/min | | | 15-60 various speed |
| NAVPENJANJE REZILA | Main drive structure | | SPIRALNO VRETENO ZOBNIK | worm wheel | SPIRALNI ZUBČANIK | worm wheel | (menjalnik hitrosti) | gear speed reducer | (mjenajč brzine) |
| ZATEZANJE REZNOG TRAKA | Workpiece clamp type | | hydraulic | HIDRAVLIČNO | hydraulic | HIDRAVLIČNO | hydraulic | hydraulic | |
| Način navpenjanja rezila | Workpiece feed type | | manual | MANUALNO (ROČNO) | manual | MANUALNO (RUČNO) | motor drive | MOTORNO | MOPTORNO |
| Način upravljanja zatezovanja obradka | Main motor power | 1.5kw | 2.2kw | 3kw | 4kw | 5.5kw | 5.5kw | 7.5kw | 11kw |
| Način upravljanja sistema zatezanja | Hydraulic motor power | | 0.55kw | | | 0.75kw | 1.1kw | 2.25kw | 3.75kw |
| Moč pog. motorja | Coolant pump power | | 0.04kw | | | 0.09kw | | 0.125kw | |
| Moč hidravl. motorja | Overall size | 1400x900x1100mm | 1880x1000x1400mm | 2000x1100x1500mm | 2400x1100x1900mm | 2800x1400x1900mm | 3500x1800x2500mm | 4130x2150x2500mm | 4580x2170x3040mm |
| Moč mot. za hladilno tekočino | N.W | 260kgs | 610kgs | 720kgs | 1400kgs | 1900kgs | 3500kgs | 4300kgs | 7500kgs |
| Moč mot. za hladilno tekočino | | | | | | | | | |
| Dimenzije stroja | | | | | | | | | |
| Neto teža stroja | | | | | | | | | |

Vse pravice pridržane ! v SLO ali JSJ jezikih !!

Sva prava zadržana u SLO i JSJ jezicima !!