


GH4235
LASNOSTI :

- ✘ Dvostebrena tračna žaga s nevpičnim dviganjem s visoko stabilnostjo
- ✘ Hitrost rezanja je spremenljivo in hidravlično
- ✘ Obdelovanec je vpet s hidravličnim vpetjem in enostaven za uporabo
- ✘ Hidravlično vpetje na triosi NI OBVEZNO je OPCIJA

KARAKTERISTIKE :

- ✘ Dvostubne pile /testere sa vertikalnim podizanjem i visokom stabilnosti
- ✘ Brzo rezanje je promienljivo i hidravlično
- ✘ Predmet rezanja je hidravlično stisnut i jednostaven je za upotrebu
- ✘ Hidravlično stezanje u tri osi je NEOBAVEZNO, kao opcija na zahtjev


GH4228A
Features:

- ✘ Double column structure vertical lifting with high stability
- ✘ The cutting speed is variable and hydraulic
- ✘ Workpiece is clamped by hydraulic control and easy to operate
- ✘ Hydraulic clamping on three axis is optional

SPECIFIKACIJE	Specification	GH4220A	GH4228A	GH4235
OBSEG REZANJA (OKROGEL) PODRUČJE REZANJA (OKRUGLO)	Cutting range (round)	φ200mm	φ200mm	φ350mm
OBSEG REZANJA (PRAVOKOTEN) PODRUČJE REZANJA (KVADRATNOG)	Cutting range (rectangular)	200x200mm	280x280mm	350x350mm
DIMENZIJE REZILA (D x Š x V) DIMENZIJE NOŽA (D x Š x V)	Blade size (LxWxT)	2800x27x0.9mm	3505x27x0.9mm	4115x34x1.1mm
Način podajanja rezila Način doziranja, rezanja, priti. rez. traka	Blade feed type	Brezstopenjska hidravlika hydraulic stepless Konstantna hidravlika		
VRST NAVPENJANJA / NAPETOSTI REZILA NAČIN NATEZANJA REZNOG TRAKA	Blade tension type	MANUALNO	manual RUČNO	
HITROST REZANJA REZIMOM BRZINA REZANJA	Blade linear speed	SPREMENLJIVO HIDRAVLIČNO	27/45/69m/min HIDRAVLIČNO, PROMJENLJIVO	
GLAVNA STRUKTURA POGONA GLAVNA STRUKTURA POGONA	Main drive structure	Delovno, vlečno kolo	worm wheel Radni, vučni točak	
PRITRIJEVANJE OBDELOVANCA STEZANJE PREDMETA REZANJA	Workpiece clamp type	HIDRAVLIČNO	hydraulic HIDRAVLIČNO	
NAČIN PODOJANJA OBDELOVANCA NAČIN DOVODA OBRATKA	Workpiece feed type	MANUALNO -RUČNO	manual RUČNO	
GLAVNI MOTOR MOČI GLAVNI MOTOR SNAGE	Main motor power	1.5kw	2.2kw	3kw
MOČ MOTORJA HIDRAVLIKE SNAGA HIDRAVLIČNOG MOTORA	Hydraulic motor power		0.55kw	
MOČ ČRPALKE za HLADILNO TEKOČINO SNAGA PUMPE za RASHLAD. TEKUČINU	Coolant pump power		0.04kw	
DIMENZIJE STROJA DIMENZIJE MAŠINE / STROJA	Overall size	1400x900x1100mm	1860x1000x1400mm	2000x1100x1500mm
N/B TEŽA N/B TEŽINA	N.W	260kgs	610kgs	720kgs