



Z3080x25/1



Z3050x16/1

SPECIFIKACIJE	Specification	Z3032x10/1	Z3040x13/1	Z3050x16/1	Z3063x20/1	Z3080x25/1
MAKSI. FI vrtanja Fi bušenja	Max. drilling dia.	32mm	40mm	50mm	63mm	80mm
Razdalja med osjo in stebrom vretena	Distance between spindle axis and column	300-1000mm	300-1300mm	350-1600mm	450-2000mm	500-2500mm
Udalj. između ose i stupa vretena						
Oddaljenost od nosa vretena do del. povr. delovne mize	Distance from spindle nose and working surface of base	250-1000mm	300-1120mm	320-1220mm	400-1600mm	550-2000mm
Udalj. nosač. vret. do rad. pov. stolice						
Premik vretena Hod vretena	Spindle travel	280mm	280mm	315mm	400mm	450mm
Konus vretena Konus vretena	Spindle taper	MT4	MT4	MT5	MT5	MT6
Hitrost vretena Brzina vretena	Spindle speed	32-2500rpm	32-2500rpm	25-2000rpm	20-1600rpm	16-1250rpm
Stev. predstav vretena - korakov	Number of spindle speed	16 steps	16 steps	16 steps	16 steps	16 steps
Broj brzina vretena - koraka						
Razpon delovneg premika vrete.	Range of spindle feed	0.10-1.25mm/r	0.10-1.25mm/r	0.04-3.20mm/r	0.04-3.20mm/r	0.04-3.20mm/r
Razpon radnog pomjer. vretena						
Stevilo hitrosti podajanja vretena	Number of spindle feed	8 steps	16 steps	16 steps	16 steps	16 steps
Broj brzina pomijeranja vretena						
Dimenzije del. mize Dim. rad. stolice	Table size	550x400x400mm	600x450x450mm	630x500x500mm	800x630x500mm	1000x800x560mm
Razdalja horizon. gibanja glave	Distance of head horizontal movement	700mm	1000mm	1250mm	1600mm	2000mm
Udaljenost horizon. pokreta glave						
Moč motorja Snaga motora	Main motor power	2.2kw	3kw	4kw	5.5kw	7.5kw
Neto teža str. Neto težina maš.	N.W	1600kgs	2500kgs	3500kgs	7000kgs	11000kgs
Dimenzije stroja Dimen. mašine	Overall size (LxWxH)	1760x800x2300mm	2100x900x2490mm	2500x1070x2840mm	3080x1250x3400mm	3730x1400x4025mm